



Key Laboratory of Agricultural Engineering
in Structure and Environment
China Agricultural University

EXHAUST FAN TEST REPORT

Model: OKM-38AT
Serial: 001001
Diameter: 940mm
Material: SMC
Power: 3.0kW
Voltage: 380V/3-Phase
Motor: Y-series
Speed: 1450rpm
Control: Thermal Overload
Winding: 3-Phase
P/N: 001001

Test Results	Actual	Standard	Remarks
1.00	1.00	1.00	OK
1.00	1.00	1.00	OK
1.00	1.00	1.00	OK
1.00	1.00	1.00	OK
1.00	1.00	1.00	OK
1.00	1.00	1.00	OK
1.00	1.00	1.00	OK
1.00	1.00	1.00	OK
1.00	1.00	1.00	OK
1.00	1.00	1.00	OK



- 38" SMC PRO EXHAUST FAN -

OKM-38AT

TARMAH VENTILATION SYSTEM MANUFACTURER SDN. BHD.

ADDRESS : LOT 2286, JALAN BUKIT PASIR, BUKIT PASIR,
83050 BATU PAHAT, JOHOR, MALAYSIA.

CONTACT : +07-341 0923(EXT.206)

FAX : +07-433 3529

EMAIL : lixfang@tarmah.com.my

CONTACT OUR SALES PERSONNEL :

TEE SHIRE LI

| 016-723 0889

HOO SEE CHOON | 016-3380248

OUR PRODUCT

SPECIFICATIONS :

IMPELLER SIZE (M/M)	900
RPM(R/M)	750
POWER (kW)	0.55
MAX AIR FLOW (M ³ /H)	36,000
NOISE (dB)	<72
VOLTAGE(V)	415
WEIGHT (KG)	45
SIZE(MM)	1060 x 1060 x 550

FEATURES :

- Design provides excellent performance without cone. Could add cone as optional.
- Cone fan line is designed to maximize performance & durability 3 aluminium cast impeller.
- Rust-free, corrosion-free, SMC housing with interior glossy for high output performance & low maintenance cost.
- Aluminium motor mounts on aluminium props
- Unique design motor mount allows quickly & easily remove all interior fan components from inside of the building.
- Standard plastic inlet shutter
- Direct drive fan standard with variable speed motor
- Self-draining, sloped housing quick and easy to clean reducing maintenance costs.
- PVC coated outlet guard - Stainless Steel Wired Guard are optional
- PVC corrosion proof shutter
- Available in any color housing finishes.